

MANUFACTURER	Lumec 640 Cure–Boivin Broisbrand QC Canada, J7G2A7
MANUFACTURER	Sea–Tac Lighting & Controls, LLC, 4439 S 134th Pl Bldg E, Tukwila, WA 98168
MODEL	Candela Series CAND2
COLOR	Dark Green (GN8–Smooth)
BASE COVER	LBC2 Base
GLOBE	(PC–C) One piece seamless clear polycarbonate
FUSE CONNECTOR KIT	Verify with technicians
FUSES	Verify with technicians
POLE HEIGHT	12 feet
POLE TYPE	(APR4U) Aluminum, Straight, Round 4”
REQUIRED OPTIONS	<p>(GFI) Duplex receptacle, WR Weather Resistant, 120 volts, ground fault interrupter, complete with an in use weatherproof aluminum cover. 15 amp, NEMA 5 15R.</p> <p>(PS) Single plant support, Fixed standard type, made of steel tubing, 1$\frac{1}{8}$” (27 mm) outside diameter, mechanically assembled to the pole, complete with standard cast aluminum decorative ball. Color to match pole.</p> <p>(SA1) Four piece cast aluminum adaptor for up to 4 road signs, designed to be mechanically secured. Color to match pole.</p>
PHOTOELECTRIC SWITCH	In electrical service cabinet provided by pole manufacturer
OPTICAL SYSTEM	(RLE5), IES Type V (Symmetrical)
SPACING	60’ o.c. unless otherwise noted on plans.
UTILITY BOX	Per plans
POWER	Per plans
CONDUIT	Per plans
LAMP	65W42LED4K
WIRING	Per plans
PERMIT	A separate electrical permit from the City is REQUIRED.

CITY OF KIRKLAND

PLAN NO. CK–R.47N



TOTEM LAKE
PEDESTRIAN LIGHT
SPECIFICATIONS